

PrO-Vet

By Centurion Scientific Ltd



25 years of
Excellence

Benchtop Centrifuges



CE marked and ISO 9001
regulated and now IVD certified too

Welcome to our new Pro-Vet range.

Designed with the busy Veterinarian in mind.

Derived from our Long running LED and LCD display centrifuges spanning over 25 years of Centrifuge manufacturing.

Simplicity of use, is paramount and places the emphasis accordingly. All are supplied with rotor or a combination of.

If the Pro-Vet does not cover your needs please look at our global web site.

Centurion have the largest range in the world of Bench top Centrifuges

Ease of Use

Using four parameters, you choose your speed and press go. One of Four LID lights will glow to show your selection. Once finished, a buzzer will sound and you simply press Lid open to retrieve your samples. Locking of the lid during a run is standard to all of this range.

We take Safety very seriously and **ALL** centrifuges have locked lid protection, you cannot open till the run has stopped.

See our User, Standard and Safety Features on the page opposite

From the start of 2014 all Centrifuges and rotors carry a 3 year warranty

That is how confident we are of our Quality and resilience

We reserve the right to make changes with ongoing research and development.

User features to Pro-Vet range	Advantages
LID display of four memories	Clarity & ease of use
Fixed acceleration & deceleration rates	Sample assistance
4 Programs of speed and time	Multi users
Sound <60Db	Quiet
Orientation acceleration rate	Prevents initial sample side deposits

Standard to Pro-Vet range	Advantages
Extra thick Stainless steel bowl	Easy clean & rust free
Port to lid	Tachometer speed certification
Alloy & steel frame with composite's	Strong light & quiet
World leading Industrial grade Inverter	Reliability & strength
Best Quality European Brushless motor	Quiet, cool & reliable
High technology airflow (ambient models)	Cooler running

Safety features to Pro-Vet range	Advantages
Multi point lid locking	Lid safety
Emergency lid release	Power failure release
Lid gas strut	Lid dropping safety
Lid lock detection	To run Lid must be shut
Imbalance detection	Easy "eye" volume loading
Overspeed Sensor	Safe detection of speed Set
inverter values	Electronic safety of speed
Barrier ring	Extra metal protection of chamber
Motor overheat sensor	Safe motor protection

Centurion Scientific Ltd centrifuges comply to all relevant EU standards for Quality and medical Devices IEC 61010 and CE conformity test marks Emission, immunity to EN/IEC 61326-1, Class B

Index

Page 4 Pro-VetHE Haematocrit centrifuge and rotors

Page 5 Pro-VetSerum centrifuge and rotors

Page 6 Pro-VetPCVs Haematocrit / Serum and rotors

Page 7 Pro-VetLA centrifuge and rotors

Page 8 Pro-VetMulti centrifuge and rotors

Page 9 Adaptors available to above

Page 10 Pro-VetCyto centrifuge, Rotors & Accessories

Page 11 Pro-Equine centrifuge, Rotor & Adaptors

PrO-VetHE



Display indicative only.

Dims HWD	235 x 235 x 350mm	
Weight	12.8 Kg (without rotor)	
Power	125 watts	
Rotor	BRK5401 & BRK5424	
Programs	Speed	Time
Haematocrit (Pcv)	12,000Rpm	300Secs
Serum 1	6,000Rpm	600Secs
Serum 2	5,000Rpm	300Secs
Urine	3,500Rpm	300Secs

Haematocrit & Microtube rotor



Rotors

BRK5401

Rotor type	24 x Capillary & 12 x 2ml
Tube size max	2 x 75mm & 11 x 40mm
Minimum speed	500 Rpm
Maximum speed	12,000 Rpm
Maximum Rcf (G)	13500
Radius	8.5
Sample tube angle (°)	0 & 60
Acceleration time (secs)	30
Deceleration time (secs)	30
Autoclaveable (frequency)	121°C (10)



BRK5424

With NEW high dome Polycarbonate lid included

24 x 2ml
11 x 50mm
500 Rpm
12,000 Rpm
13500
8.5
45
20
20
121°C (20)



Accessories



8003 PCV reader



8014 Sealing clay

Part Number	Description
8012	Plain Capillary tubes pack 1000
8013	Heperanised Capillary tubes pack 1000

PrO-VetSerum



Display indicative only.

Dims HWD235 x 235 x 350mm

Weight.....12.8 Kg (without rotor)

Power.....125 watts

Rotor.....BRK5408

Programs	Speed	Time
Serum 1	6,000Rpm	180Secs
Serum 2	6,000Rpm	240Secs
Serum 3	5,000Rpm	300Secs
Urine	3,500Rpm	300Secs

Serum Rotor to 15ml *Reducers available for 5 & 10ml*



Rotors

BRK5408

Rotor type	8 x 15ml
Tube size max	17 x 120mm
Minimum speed	500 Rpm
Maximum speed	6000 Rpm
Maximum Rcf (G)	3500
Radius max cms	8.50
Sample tube angle (o)	30
Acceleration time (secs)	30
Deceleration time (secs)	30
Autoclaveable (frequency)	121°C (20)

Reducers



Rotor

BRK5408

Part number

RM05 (5ml)

Tube size max

13 x 80mm

Part number

RM10 (10ml)

Tube size max

16 x 100mm

PrO-VetPCVs



Display indicative only.

Dims HWD235 x 235 x 350mm

Weight.....12.8 Kg (without rotor)

Power.....125 watts

Rotor.....BRK5401 & BRK5408

Program	Speed	Time
Haematocrit (Pcv)	12,000Rpm	300Secs
Serum 1	6,000Rpm	600Secs
Serum 2	5,000Rpm	300Secs
Urine	3,500Rpm	300Secs
Program	Speed	Time
Serum 1	6,000Rpm	180Secs
Serum 2	6,000Rpm	240Secs
Serum 3	5,000Rpm	300Secs
Urine	3,500Rpm	300Secs

Serum (15ml max) & Haematocrit Rotor



Rotors

	BRK5401	BRK5408
Rotor type	24 x Capillary & 12 x 2ml	8 x 15ml
Tube size max	2 x 75mm & 11 x 40mm	17 x 120mm
Minimum speed	500 Rpm	500 Rpm
Maximum speed	12,000 Rpm	6000 Rpm
Maximum Rcf (G)	13500	3500
Radius max cms	8.5	8.50
Sample tube angle (°)	0 & 60	30
Acceleration time (secs)	30	30
Deceleration time (secs)	30	30
Autoclaveable (frequency)	121°C (10)	121°C (20)

Accessories



8003 PCV reader



8014 Sealing clay

Part Number	Description
8012	Plain Capillary tubes pack 1000
8013	Heperanised Capillary tubes pack 1000

PrO-VetLA



Display indicative only.

Dims HWD275 x 325 x 470mm

Weight.....21.8 Kg (without rotor)

Power.....175 watts

Rotor.....BRK5508M & BRK5412
or BRK5406

Program 5508M Speed		Time
Serum 1	4,000Rpm	400Secs
Serum 2	3,500Rpm	300Secs
Serum 3	3,000Rpm	300Secs
Urine	2,500Rpm	400Secs
Program 5412/06 Speed		Time
Seerum 1	4,000Rpm	480Secs
Sperm	3,000Rpm	840Secs
Faeces	3,000Rpm	600Secs
Urine	2,750Rpm	500Secs

Swing Out Rotor Fixed Angle 12 x 15 or 6 x 50ml



Rotors

	BRK5508M
Rotor type	8 x 10ml
Tube size max	15 x 100mm
Minimum speed	500 Rpm
Maximum speed	4,000 Rpm
Maximum Rcf (G)	2200
Radius max cms	12.3
Sample tube angle (o)	0
Acceleration time (secs)	25
Deceleration time (secs)	25
Autoclaveable (frequency)	121°C (20)



CHOICE OF ONE

	BRK5412	BRK5406
	12 x 15ml	6 x 50ml
	17 x 120mm	30 x 120mm
	500 Rpm	500 Rpm
	6,000 Rpm	6,000 Rpm
	3800	3800
	9.5	9.5
	30	30
	25	25
	25	25
	121°C (20)	121°C (20)

Reducers



Rotor

Part number
Tube size max
Part number
Tube size max

BRK5412

BRK5406

RM05 (5ml)

RM15 (15ml)

13 x 80mm

17 x 120mm

RM10 (10ml)

RM25 (25ml)

16 x 100mm

25 x 100mm

PrO-VetMulti



Display indicative only.

Dims HWD275 x 325 x 470mm

Weight.....21.8 Kg (without rotor)

Power.....175 watts

Rotor.....BRK5401 & BRK5505

Program 5401	Speed	Time
Haematocrit (Pcv)	12,000Rpm	300Secs
Serum 1	6,000Rpm	600Secs
Serum 2	5,000Rpm	300Secs
Urine	3,500Rpm	300Secs
Program 5505	Speed	Time
Sperm	3,500Rpm	480Secs
Sperm	1,275Rpm	840Secs
Faeces	3,000Rpm	600Secs
Urine	2,500Rpm	500Secs

Swing Out Rotor

4 x 100ml max

Adaptors required see page 9



Rotor

BRK5505

Rotor type	4 x 100ml
Tube size max	45 x 100mm
Minimum speed	500 Rpm
Maximum speed	4,000 Rpm
Maximum Rcf (G)	2200
Radius max cms	12.3
Sample tube angle (o)	0
Acceleration time (secs)	25
Deceleration time (secs)	25
Autoclaveable (frequency)	121°C (20)

Sealed lids available set 4 Part Nos 5419

Haematocrit (Pcv) and 2ml



Rotors

BRK5401

Rotor type	24 x Capillary & 12 x 2ml
Tube size max	2 x 75mm & 11 x 40mm
Minimum speed	500 Rpm
Maximum speed	12,000 Rpm
Maximum Rcf (G)	13500
Radius max cms	8.5
Sample tube angle (o)	0 & 60
Acceleration time (secs)	30
Deceleration time (secs)	30
Autoclaveable (frequency)	121°C (10)

Accessories




8003 PCV reader



8014 Sealing clay

Part Number	Description
8012	Plain Capillary tubes pack 1000
8013	Heperanised Capillary tubes pack 1000

Adaptors for Swing out rotors					Adaptors	
Tube type	Shape	Capacity	Size	To fit rotor	BRK5505	
				Part nos	Nos of tubes per rotor	
			WxH (mm)			
	Micro with cap	point	0.5ml	8x20	AM505	36
	Micro with cap	point	1.5ml	11x38	AM520	24
	Micro with cap	point	2.0ml	11x38	AM520	24
	Micro with cap	point	0.2ml	6x20	AM502	36
	Micro with cap	point	0.4ml	6x30	AM504	36
	Plain No cap	round	1ml	6x45	AR501	36
	Plain No cap	round	3ml	10x60	AR503	28
	Plain No cap	round	5ml	12x75	AR505 *	28
	Plain No cap	round	6ml	12x82	AR505 *	28
	Plain No cap	round	7ml	12x100	AR507 *	28
	Plain No cap	round	9/10ml	14x100	AR509 *	24
	Plain No cap	round	15ml	17x100	AR515 *	8
	Plain No cap	round	25ml	24x100	AR525 *	8
	Plain No cap	round	50ml	34x100	AR550 *	4
	Plain No cap	round	100ml	45x100	AR5100 *	4
	Plain No cap	round	150ml	52x100	See K241/R	
	Plain No cap	round	250ml	62x100	See K241/R	
	Falcon with cap	Point	15ml	17x120	AF515 *	8
	Falcon with cap	Point	50ml	29x115	AF550 *	4
	Falcon with cap	Point	175ml	61x118	See K241/R	
	Corning with cap*	Point	250ml	60x172	See K242/R	
	Corning with cap*	Point	500ml	98x148	See K242/R	
	Falcon with cap	Square	12ml	17x100	AFS512 *	8
	Falcon with cap	Square	25ml	25x90	AFS525	4
	Falcon with cap	Square	30ml	25x110	AFS530	4
	Falcon with cap	Square	50ml	29x115	AFS550 *	4
	Falcon with cap	Square	15ml	17x120	N/A	N/A
	Nalgene/Dakriddle	Round	10ml	16x80	ANO510 *	8
	Nalgene/Dakriddle	Round	30ml	26x95	ANO530 *	4
	Nalgene/Dakriddle	Round	50ml	29x107	ANO550 *	4
	Nalgene/Dakriddle	Round	85ml	38x106	ANO585	4
	Nalgene/Dakriddle*	Flat	250ml	62x130	See K241/R	
	Nalgene/Dakriddle*	Flat	750ml	98x153	See K243/R	
	Monovette	Square	1.1-1.4ml	8x82	AM5014	24
	Monovette	Square	2.7-3ml	11x82	AM503	24
	Monovette	Square	2.6-2.9ml	13x81	AM529	24
	Monovette	Square	4.5-5ml	11x108	AM503 *	24
	Monovette	Square	7.5-8.2ml	13x106	AM579 *	24
	Monovette	Square	4-5.5ml	15x92	AM550 *	20
	Monovette	Square	7.5-8.2ml	15x108	AM550 *	20
	Monovette	Square	9-10.0ml	16x108	AM590 *	20
	Vacutainer	Round	1.6-5.0ml	13x75	AV516 *	24
	Vacutainer	Round	4-7.0ml	13x100	AV550 * INCLUDED	16
	Vacutainer	Round	8.5-10.0ml	16x100	AV580 *	12

Note:- We cannot be held responsible if the tube manufacturers change design and/or size of the tube.

* Limited capacity with sealed bucket lids (B5419 and B5319).

PrO-VetCyto



Display indicative only

Dims HWD	275 x 325 x 470mm		
Weight	21.8 Kg (without rotor)		
Power	175 Watts		
Rotor	BRK4420 or BRK4430		
Programs	Speed	Time Slow	
	200RPM	600 Secs	
	500RPM	600 Secs	
	1,000RPM	500 Secs	
Medium	2,000RPM	500 Secs	
High			
Maximum			

Rotor Cytology

Using centrifugal force to separate and deposit a monolayer of cells onto slides whilst maintaining integrity within a clearly defined area **FROM ANY FLUID MATRIX**. Cyto centrifugation also constructively flattens cells for excellent nuclear presentation.

Applications include Cytology, Histology, Haematology, Oncology, Immunochemistry, Serology and Microbiology.

Offering samples from 0.1ml to 6ml and an extensive range of accessories we have your Cytology needs covered.



Rotor	4420	4430
Rotor Type	4 x 0.2ml to 6ml	8 x 0.2 to 6ml
Holders	Single or Double	Single or Double
Minimum Speed	200 RPM	200 RPM
Maximum Speed	2,000 RPM	2,000 RPM
Maximum RCF (g)	550	550
Radius max	12 CM	12 CM
Sample tube angle	0	0
Acceleration time (secs)	25	25
Deceleration time (secs)	25	25
Autoclaveable (frequency)	121°C (10)	121°C (10)



4446 Double sample holder with card (up to 1ml)



4444 Double sample holder with card (up to 1ml)



4600 Double sample holder with card (up to 6ml)



4446 Stainless steel clips

Accessories

PrO-Equine

Equine Centrifuge for AI, Horse semen, Embryo Transfer, Faeces & Blood Work.



Display indicative only

Dims HWD	275mm x 325mm x 470mm
Weight	21.8 Kg
Power	125 Watts
Rotor	BRK5505 Swing Out Rotor
Speed	500 - 4000 RPM
RFC Max	2200G
Memory	10 Programs
Accel Rates	10 Programs
Decel Rates	10 Programs

Swing Out Rotor



Rotor

Rotor Type	4 x100ml Swing Out
Tube Size Max	45 x 100mm
Minimum Speed	500 RPM
Maximum Speed	4000 RPM
Maximum RCF (g)	2200
Radius max	12.3 CM
Sample tube angle	0
Acceleration time (secs)	25
Deceleration time (secs)	25
Autoclaveable (frequency)	121 C (20)

BRK5505

4 x100ml Swing Out
45 x 100mm
500 RPM
4000 RPM
2200
12.3 CM
0
25
25
121 C (20)

Included



AF515

Capacity
8 x 15ml



AF550

Capacity
4 x 50ml

Adaptors available - see page 9



MADE IN BRITAIN
DISTRIBUTED WORLDWIDE

**To review all our ranges
please visit our global website**



www.centurionscientificglobal.com

